

## PRODUCT-DETAILS

# FC-S5/250 400V-6h

## Ind. P&S#FC-S5/250 400V-6h



### General Information

|                       |                                                                                                                                                                                                                                                                                    |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | FC-S5/250 400V-6h                                                                                                                                                                                                                                                                  |
| Product ID            | 2CMA103315R1000                                                                                                                                                                                                                                                                    |
| EAN                   | 7392696033152                                                                                                                                                                                                                                                                      |
| Catalog Description   | Ind. P&S#FC-S5/250 400V-6h                                                                                                                                                                                                                                                         |
| Long Description      | Industrial connectors, 3P+N+E, IP67, 250 A, 200 ... 250 V, The compact C-Line connectors have a robust plastic housing and are perfect for applications with limited space conditions as well as for certain industries (chemistry, food industry). Designed for high temperature. |

### Ordering

|                        |                  |
|------------------------|------------------|
| EAN                    | 7392696033152    |
| Country of Origin      | Switzerland (CH) |
| Minimum Order Quantity | 1 piece          |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 190 mm |
| Product Net Height | 185 mm |
| Product Net Weight | 3.6 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 407 mm        |
| Package Level 1 Depth / Length | 407 mm        |
| Package Level 1 Height         | 187 mm        |
| Package Level 1 Gross Weight   | 3.6 kg        |
| Package Level 1 EAN            | 7392696033152 |
| Package Level 1 Units          | box 1 piece   |

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | NoDecNee        |
| Environmental Information         | 2CMC000074M0000 |

## Additional Information

|                            |                                  |
|----------------------------|----------------------------------|
| Additional Information     | 3P+N+E                           |
| Ambient Temperature        | -40 ... 100 °C                   |
| Cable Diameter             | 45 ... 65 mm                     |
| Cable Entry Position       | Anti-kink sleeve                 |
| Color                      | Red                              |
| Connection Type            | Screw                            |
| Degree of Protection       | IP67                             |
| Frequency (f)              | 50 Hz<br>60 Hz                   |
| Function                   | Connector                        |
| Housing Material           | Plastic                          |
| Invoice Description        | Ind. P&S#FC-S5/250 400V-6h       |
| Number of Poles            | 5                                |
| Order Multiple             | 1 piece                          |
| Product Main Type          | FC                               |
| Product Name               | High current connector           |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 250 A                            |
| Rated Voltage ( $U_r$ )    | 200/346 ... 240/415 V            |
| Standards                  | IEC 60309-1, -2                  |
| Sub-Function               | C-line                           |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 9005 - Jet Black             |

## Classifications

|        |          |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

---

## Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

