

PRODUCT-DETAILS

# FCP-S4/250 230V-9h

## Ind. P&S#FCP-S4/250 230V-9h



### General Information

Extended Product Type	FCP-S4/250 230V-9h
Product ID	2CMA103359R1000
EAN	7392696033596
Catalog Description	Ind. P&S#FCP-S4/250 230V-9h
Long Description	Panel mounted socket outlets, 3P+E, IP67, 250 A, 380 ... 415 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connectors also suitable for marine applications. Aluminum housing. Designed for high temperature.

### Ordering

EAN	7392696033596
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

### Dimensions

Product Net Width	275 mm
Product Net Height	230 mm

Product Net Weight	6.8 kg
--------------------	--------

### Container Information

Package Level 1 Width	352 mm
Package Level 1 Depth / Length	352 mm
Package Level 1 Height	232 mm
Package Level 1 Gross Weight	6.8 kg
Package Level 1 EAN	7392696033596
Package Level 1 Units	box 1 piece

### Certificates and Declarations (Document Number)

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

### Additional Information

Additional Information	3P+E
Ambient Temperature	-40 ... 100 °C
Color	Blue
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Aluminum
Invoice Description	Ind. P&S#FCP-S4/250 230V-9h
Mounting Holes	127x127
Number of Poles	4
Order Multiple	1 piece
Product Main Type	FCP
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current ( $I_n$ )	250 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	200...250 V
Standards	IEC 60309-1, -2
Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

### Classifications

eClass	27440504
UNSPSC	39120000

---

---

## Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

