

## PRODUCT-DETAILS

# FCP-S4/400 690V-5h

## Ind. P&S#FCP-S4/400 690V-5h



### General Information

|                       |                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | FCP-S4/400 690V-5h                                                                                                                                                                                                                                                                                                                                                      |
| Product ID            | 2CMA103372R1000                                                                                                                                                                                                                                                                                                                                                         |
| EAN                   | 7392696033725                                                                                                                                                                                                                                                                                                                                                           |
| Catalog Description   | Ind. P&S#FCP-S4/400 690V-5h                                                                                                                                                                                                                                                                                                                                             |
| Long Description      | Panel mounted socket outlets, 3P+E, IP67, 400 A, 380 ... 415 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connectors also suitable for marine applications. Aluminum housing. Designed for high temperature. |

### Ordering

|                        |                  |
|------------------------|------------------|
| EAN                    | 7392696033725    |
| Country of Origin      | Switzerland (CH) |
| Minimum Order Quantity | 1 piece          |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 275 mm |
| Product Net Height | 230 mm |

|                    |        |
|--------------------|--------|
| Product Net Weight | 6.8 kg |
|--------------------|--------|

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 352 mm        |
| Package Level 1 Depth / Length | 352 mm        |
| Package Level 1 Height         | 232 mm        |
| Package Level 1 Gross Weight   | 6.8 kg        |
| Package Level 1 EAN            | 7392696033725 |
| Package Level 1 Units          | box 1 piece   |

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | NoDecNee        |
| Environmental Information         | 2CMC000074M0000 |

## Additional Information

|                            |                                  |
|----------------------------|----------------------------------|
| Additional Information     | 3P+E                             |
| Ambient Temperature        | -40 ... 100 °C                   |
| Color                      | Black                            |
| Connection Type            | Screw                            |
| Degree of Protection       | IP67                             |
| Frequency (f)              | 50 Hz<br>60 Hz                   |
| Function                   | Outlet                           |
| Housing Material           | Aluminum                         |
| Invoice Description        | Ind. P&S#FCP-S4/400 690V-5h      |
| Mounting Holes             | 127x127                          |
| Number of Poles            | 4                                |
| Order Multiple             | 1 piece                          |
| Product Main Type          | FCP                              |
| Product Name               | Panel mounted socket             |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 400 A                            |
| Rated Frequency (f)        | 50...60 Hz                       |
| Rated Voltage ( $U_r$ )    | 600 ... 690 V                    |
| Standards                  | IEC 60309-1, -2                  |
| Sub-Function               | B-line                           |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 7001 - Silver Grey           |

## Classifications

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

---

Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

