

PRODUCT-DETAILS

FCPA-S5/250 690V-5h

Ind. P&S#FCPA-S5/250 690V-5h



General Information

Extended Product Type	FCPA-S5/250 690V-5h
Product ID	2CMA103397R1000
EAN	7392696033978
Catalog Description	Ind. P&S#FCPA-S5/250 690V-5h
Long Description	Panel mounted socket outlets, 3P+N+E, IP67, 250 A, 380 ... 415 V

Ordering

EAN	7392696033978
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	240 mm
Product Net Height	242 mm
Product Net Weight	4.6 kg

Container Information

Package Level 1 Width	464 mm
-----------------------	--------

Package Level 1 Depth / Length	464 mm
Package Level 1 Height	244 mm
Package Level 1 Gross Weight	4.6 kg
Package Level 1 EAN	7392696033978
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 100 °C
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Invoice Description	Ind. P&S#FCPA-S5/250 690V-5h
Mounting Holes	120x120
Number of Poles	5
Order Multiple	1 piece
Product Main Type	FCPA
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	250 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	347/600 ... 400/690 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

