

## PRODUCT-DETAILS

# CUMI-S5/400 690V-5h

## Ind. P&S#CUMI-S5/400 690V-5h



### General Information

|                       |                                                                                                                     |
|-----------------------|---------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | CUMI-S5/400 690V-5h                                                                                                 |
| Product ID            | 2CMA103497R1000                                                                                                     |
| EAN                   | 7392696034975                                                                                                       |
| Catalog Description   | Ind. P&S#CUMI-S5/400 690V-5h                                                                                        |
| Long Description      | Connector Unit with Mechanical Interlock, yellow painted steel enclosure, 1200X800X375, CUMI-S5/400 690V-5h, 3P+N+E |

### Ordering

|                        |                  |
|------------------------|------------------|
| EAN                    | 7392696034975    |
| Country of Origin      | Switzerland (CH) |
| Minimum Order Quantity | 1 piece          |

### Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 550 mm  |
| Product Net Height | 362 mm  |
| Product Net Weight | 47.1 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 883 mm        |
| Package Level 1 Depth / Length | 883 mm        |
| Package Level 1 Height         | 364 mm        |
| Package Level 1 Gross Weight   | 47.1 kg       |
| Package Level 1 EAN            | 7392696034975 |
| Package Level 1 Units          | box 1 piece   |

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | NoDecNee        |
| Environmental Information         | 2CMC000074M0000 |

## Additional Information

|                            |                                          |
|----------------------------|------------------------------------------|
| Additional Information     | 3P+N+E                                   |
| Ambient Temperature        | -40 ... 70 °C                            |
| Cable Diameter             | 20 ... 65 mm                             |
| Cable Entry Position       | Up                                       |
| Color                      | Black                                    |
| Connection Type            | Screw Clamp                              |
| Degree of Protection       | IP55                                     |
| Frequency (f)              | 50 Hz<br>60 Hz                           |
| Function                   | Connector Unit with Mechanical Interlock |
| Housing Material           | Steel                                    |
| Invoice Description        | Ind. P&S#CUMI-S5/400 690V-5h             |
| Mounting Holes             | 515x630                                  |
| Number of Poles            | 5                                        |
| Order Multiple             | 1 piece                                  |
| Product Main Type          | CUMI                                     |
| Product Name               | Connector Unit with Mechanical Interlock |
| Rated Current ( $I_n$ )    | 400 A                                    |
| Rated Voltage ( $U_r$ )    | 347/600 ... 400/690 V                    |
| Standards                  | IEC 60309-1, -2                          |
| Sub-Function               | B-line                                   |
| Suitable for Product Class | IEC Industrial Plugs and Sockets         |
| Instructions and Manuals   | 2CMC700014C0016                          |
| RAL Number                 | RAL 1004 - Golden Yellow                 |

## Classifications

|        |          |
|--------|----------|
| eClass | 27440508 |
| UNSPSC | 39120000 |

---

## Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

