

---

PRODUCT-DETAILS

# 432EP6B

## Industrial plugs, 3P+N+E, 32 A, 200/346 ... 240/415V




---

### General Information

Extended Product Type	432EP6B
Product ID	2CMA103593R1000
EAN	7392696035934
Catalog Description	Industrial plugs, 3P+N+E, 32 A, 200/346 ... 240/415V
Long Description	Industrial Plug, 432EP6B, 32 A, 3P+N+E, 6 hour, Industrial plugs, 3P+N+E, 32 A, 200/346 ... 240/415V,

---

### Ordering

E-Number (Sweden)	E2417575
E-Number (Finland)	2420243
E-Number (Norway)	1540765
EAN	7392696035934
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

---

### Dimensions

Product Net Width	79 mm
Product Net Height	88 mm

Product Net Weight	0.24 kg
--------------------	---------

## Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696036177
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1100 kg
Package Level 2 EAN	7392696066976
Package Level 2 Units	pallet (lift) 450 piece

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificates and Declarations (Document Number)

CB Certificate	2CHC660167X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1617364
REACH Declaration	2CMC700005D0001

## Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm <sup>2</sup>
Cable Diameter	22 mm
Cable Entry Position	Swivel
Color	Red
Connection Type	Screw
Cover Color	Black
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz

Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#432EP6B
Number of Poles	5
Order Multiple	10 piece
Product Main Type	EP
Product Name	Industrial Plug
Protection Type	Splashproof
Rated Current ( $I_n$ )	32 A
Rated Voltage ( $U_r$ )	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

## Classifications

eClass	27440509
UNSPSC	39120000

## Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Plugs

