

PRODUCT-DETAILS

463C5W

Ind. P&S#463C5W



General Information

Extended Product Type	463C5W
Product ID	2CMA126664R1000
EAN	7392696266642
Catalog Description	Ind. P&S#463C5W
Long Description	Connector, earthing sleeve position 5h, rated current 63A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Black

Ordering

E-Number (Sweden)	99090212
E-Number (Finland)	2420414
EAN	7392696266642
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	108 mm
Product Net Height	112 mm
Product Net Weight	0.88 kg

Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	0.88 kg
Package Level 1 EAN	7392696266642
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	78.08 kg
Package Level 2 EAN	7392696067805
Package Level 2 Units	pallet (lift) 66 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614200
UL Certificate	E163435-19950105-UL_cert_C_R
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm ²
Cable Diameter	17 ... 35 mm
Cable Entry Position	Anti-kink sleeve
Color	Black
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Connector

Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463C5W
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I_n)	63 A
Rated Voltage (U_r)	347/600 ... 400/690 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Connectors
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

