

## PRODUCT-DETAILS

# 432RAU5

Panel mounted socket outlets, 3P+N+E, 32 A,  
347/600 ... 400/690 V



## General Information

|                       |                                                                                                                                                     |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 432RAU5                                                                                                                                             |
| Product ID            | 2CMA126679R1000                                                                                                                                     |
| EAN                   | 7392696266796                                                                                                                                       |
| Catalog Description   | Panel mounted socket outlets, 3P+N+E, 32 A, 347/600 ... 400/690 V                                                                                   |
| Long Description      | Panel mounted socket, earthing sleeve position 5h, rated current 32A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Black |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 99090227            |
| EAN                    | 7392696266796       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

## Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 110 mm  |
| Product Net Height | 110 mm  |
| Product Net Weight | 0.28 kg |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 188 mm                  |
| Package Level 1 Depth / Length | 175 mm                  |
| Package Level 1 Height         | 428 mm                  |
| Package Level 1 Gross Weight   | 2.8 kg                  |
| Package Level 1 EAN            | 7392696267151           |
| Package Level 1 Units          | box 10 piece            |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 692 kg                  |
| Package Level 2 EAN            | 7392696067959           |
| Package Level 2 Units          | pallet (lift) 240 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1613211         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                       |
|------------------------|-----------------------|
| Additional Information | 3P+N+E                |
| Ambient Temperature    | -25 ... 40 °C         |
| Cable Cross-Section    | 2.5 ... 10 mm²        |
| Cable Diameter         | 13 ... 21.5 mm        |
| Color                  | Black                 |
| Connection Type        | Screw                 |
| Degree of Protection   | IP44                  |
| Frequency (f)          | 50 Hz<br>60 Hz        |
| Function               | Panel mounted socket  |
| Housing Material       | plastic (PA)          |
| Invoice Description    | Ind. P&S#432RAU5      |
| Mounting Holes         | 85x85                 |
| Mounting Type          | Unified angled flange |
| Number of Poles        | 5                     |

|                            |                                  |
|----------------------------|----------------------------------|
| Order Multiple             | 10 piece                         |
| Product Main Type          | ERAU                             |
| Product Name               | Panel mounted socket             |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 32 A                             |
| Rated Frequency (f)        | 50...60 Hz                       |
| Rated Voltage ( $U_r$ )    | 347/600 ... 400/690 V            |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC00058M0001                   |
| Installation Manual        | 2CMC00058M0001                   |
| RAL Number                 | RAL 7001 - Silver Grey           |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39121406 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

