

PRODUCT-DETAILS

416MM5

Switched Interlocked Socket Outlet, metal, 5h,
16A, IP44, 3P+N+E



General Information

Extended Product Type	416MM5
Product ID	2CMA126695R1000
EAN	7392696266956
Catalog Description	Switched Interlocked Socket Outlet, metal, 5h, 16A, IP44, 3P+N+E
Long Description	Switched Interlocked Socket Outlet, metal, earthing sleeve position 5h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Black

Ordering

E-Number (Sweden)	99090243
EAN	7392696266956
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	135 mm
Product Net Height	125 mm
Product Net Weight	1.35 kg

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	1.35 kg
Package Level 1 EAN	7392696266956
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	254.9 kg
Package Level 2 EAN	7392696067621
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1515100
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Entry Position	Top and bottom
Cable Outlets Per Side	1xM25+1xM32
Color	Black
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Switched Interlocked Socket Outlet, metal
Housing Material	Aluminium
Invoice Description	Ind. P&S#416MM5
Mounting Holes	165x91
Mounting Type	Vertical

Number of Poles	5
Order Multiple	1 piece
Product Main Type	CMM
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	Switched Interlocked
Rated Current (I_n)	16 A
Rated Voltage (U_r)	347/600 ... 400/690 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Suitable For	Switched Interlocked Socket Outlets in Metal
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000034M0001
Installation Manual	2CMC000034M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets in Metal

