

## PRODUCT-DETAILS

# BW625TPN

## BW625TPN Enclosed Switch Disconnecter



### General Information

|                       |                                       |
|-----------------------|---------------------------------------|
| Extended Product Type | BW625TPN                              |
| Product ID            | 2CMA142406R1000                       |
| EAN                   | 7392696424066                         |
| Catalog Description   | BW625TPN Enclosed Switch Disconnecter |

#### Long Description

The enclosure of the ABB's side controlled enclosed switches are made of rigid polycarbonate. The enclosure is UV protected, and protected against low pressure water jets (IP65), and hence built for outdoor and indoor use. The enclosure for 6 pole switches is available in different colors, grey and yellow. The cable entries are of none threaded knock out types with holes for 2 parallel cables, both from top and bottom. Membrane grommets and locking nuts are included (IP54). The handle is padlockable and made for one padlock. The cover is interlocked. The switch includes neutral and PE terminal. The terminals are easily accessible for easy installation.

### Ordering

|                        |               |
|------------------------|---------------|
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85363030      |
| Country of Origin      | Bulgaria (BG) |

### Popular Downloads

|                                   |                   |
|-----------------------------------|-------------------|
| Data Sheet, Technical Information | 1SCC340015C0201   |
| Mechanical Drawings               | BAS3131965D25.stp |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 190 mm  |
| Product Net Height         | 130 mm  |
| Product Net Depth / Length | 65 mm   |
| Product Net Weight         | 0.54 kg |

## Technical

|                                                    |                                                                                                    |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Rated Operational Current AC-22A ( $I_e$ )         | (380 ... 415 V) 25 A<br>(690 V) 16 A                                                               |
| Rated Operational Power AC-23A ( $P_e$ )           | (380 ... 415 V) 7.5 kW                                                                             |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | 32 A                                                                                               |
| Conventional Thermal Current ( $I_{the}$ )         | Fully Enclosed 25 A                                                                                |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | 8 kV                                                                                               |
| Rated Insulation Voltage ( $U_i$ )                 | acc. to IEC/EN 60664-1 690 V                                                                       |
| Rated Operational Voltage                          | Main Circuit 690 V                                                                                 |
| Handle Color                                       | Grey                                                                                               |
| Handle Type                                        | Side-operated handle                                                                               |
| Standards                                          | IEC 60947-1, -3                                                                                    |
| Number of Poles                                    | 6                                                                                                  |
| Connecting Capacity Main Circuit                   | Screw Clamp 0.75...10 mm <sup>2</sup><br>Screw Clamp / PE Terminal 1pcs, 0.75...10 mm <sup>2</sup> |
| Cable Entry Position                               | Up/Down                                                                                            |
| Cable Outlets Per Side                             | 2xø25.5+ø16.5 / 2xø25.5+ø16.5                                                                      |
| Degree of Protection                               | acc. to IEC 60529 IP65                                                                             |
| Enclosure Material                                 | Plastic                                                                                            |
| Maximum Mounted Auxiliary Contacts                 | 2 NO, 0 NC                                                                                         |
| Mounted Auxiliary Contacts                         | 0 NO, 0 NC                                                                                         |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC340062D2702 |
| RoHS Information               | 2CMC300025D0001 |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 132 mm        |
| Package Level 1 Depth / Length | 191 mm        |
| Package Level 1 Height         | 68 mm         |
| Package Level 1 Gross Weight   | 0.54 kg       |
| Package Level 1 EAN            | 7392696424066 |

## Classifications

|                       |                                                            |
|-----------------------|------------------------------------------------------------|
| Object Classification | Q                                                          |
| Code                  | 2CMT005069                                                 |
| ETIM 4                | EC000216 - Switch disconnecter                             |
| ETIM 5                | EC000216 - Switch disconnecter                             |
| ETIM 6                | EC000216 - Switch disconnecter                             |
| ETIM 7                | EC000216 - Switch disconnecter                             |
| UNSPSC                | 39120000                                                   |
| WEEE Category         | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

