

## PRODUCT-DETAILS

# 316P5W

## Ind. P&S#316P5W



### General Information

|                       |                                                                                                                            |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 316P5W                                                                                                                     |
| Product ID            | 2CMA166474R1000                                                                                                            |
| EAN                   | 7392696664745                                                                                                              |
| Catalog Description   | Ind. P&S#316P5W                                                                                                            |
| Long Description      | Plug, earthing sleeve position 5h, rated current 16A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Black |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416244            |
| E-Number (Finland)     | 2421633             |
| E-Number (Norway)      | 2416244             |
| EAN                    | 7392696664745       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 79 mm   |
| Product Net Height | 79 mm   |
| Product Net Weight | 0.24 kg |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 95 mm                   |
| Package Level 1 Depth / Length | 95 mm                   |
| Package Level 1 Height         | 175 mm                  |
| Package Level 1 Gross Weight   | 0.24 kg                 |
| Package Level 1 EAN            | 7392696664745           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 116 kg                  |
| Package Level 2 EAN            | 7392696068741           |
| Package Level 2 Units          | pallet (lift) 400 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                               |
|---------------------------------|-------------------------------|
| Additional Information          | 3P+E                          |
| Ambient Temperature             | -25 ... 40 °C                 |
| Cable Cross-Section             | 1 ... 2.5 mm²                 |
| Cable Diameter                  | 13 ... 17 mm                  |
| Cable Entry Position            | Cable entry compression gland |
| Color                           | Black                         |
| Connection Type                 | Screw                         |
| Degree of Protection            | IP67<br>IP69                  |
| Frequency (f)                   | 50 Hz<br>60 Hz                |
| Function                        | Plug                          |
| Housing Material                | Thermoplastic (PBT)           |
| Invoice Description             | Ind. P&S#316P5W               |
| Number of Poles                 | 4                             |
| Order Multiple                  | 1 piece                       |
| Product Main Type               | TP                            |
| Product Name                    | Industrial Plug               |
| Protection Type                 | Watertight                    |
| Rated Current (I <sub>n</sub> ) | 16 A                          |
| Rated Voltage (U <sub>r</sub> ) | 600 ... 690 V                 |

|                            |                                  |
|----------------------------|----------------------------------|
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Plugs                            |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 7001 - Silver Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Plugs

