


PRODUCT-DETAILS

316P11W

Ind. P&S#316P11W



General Information

Extended Product Type	316P11W
Product ID	2CMA166484R1000
EAN	7392696664844
Catalog Description	Ind. P&S#316P11W
Long Description	Plug, earthing sleeve position 11h, rated current 16A, IP67 watertight, 3-poles+earth, frequency 60 Hz, color code Red

Ordering

E-Number (Sweden)	2416249
E-Number (Finland)	2416249
E-Number (Norway)	2416249
EAN	7392696664844
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	79 mm
Product Net Height	79 mm

Product Net Weight	0.24 kg
--------------------	---------

Container Information

Package Level 1 Width	95 mm
Package Level 1 Depth / Length	95 mm
Package Level 1 Height	175 mm
Package Level 1 Gross Weight	0.24 kg
Package Level 1 EAN	7392696664844
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	116 kg
Package Level 2 EAN	7392696068796
Package Level 2 Units	pallet (lift) 400 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm ²
Cable Diameter	13 ... 17 mm
Cable Entry Position	Cable entry compression gland
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	60 Hz
Function	Plug
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#316P11W

Number of Poles	4
Order Multiple	1 piece
Product Main Type	TP
Product Name	Industrial Plug
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Voltage (U_r)	440 ... 460 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Plugs
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Plugs

