

PRODUCT-DETAILS

316C2W

Ind. P&S#316C2W



General Information

Extended Product Type	316C2W
Product ID	2CMA166546R1000
EAN	7392696665469
Catalog Description	Ind. P&S#316C2W
Long Description	Connector, earthing sleeve position 2h, rated current 16A, IP67 watertight, 3-poles+earth, frequency 300-500 Hz, color code Green

Ordering

E-Number (Sweden)	2416365
E-Number (Finland)	2416365
E-Number (Norway)	2416365
EAN	7392696665469
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	78 mm
Product Net Height	88 mm

Product Net Weight	0.31 kg
--------------------	---------

Container Information

Package Level 1 Width	95 mm
Package Level 1 Depth / Length	95 mm
Package Level 1 Height	175 mm
Package Level 1 Gross Weight	0.31 kg
Package Level 1 EAN	7392696665469
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	144 kg
Package Level 2 EAN	7392696069106
Package Level 2 Units	pallet (lift) 400 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614200
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm ²
Cable Diameter	13 ... 17 mm
Cable Entry Position	Cable entry compression gland
Color	Green
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	>300 ... 500 Hz
Function	Connector
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#316C2W
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I _n)	16 A
Rated Frequency (f)	300 ... 500 Hz
Rated Voltage (U _r)	50 ... 500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Connectors
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

