

## PRODUCT-DETAILS

# 232BAU12W

## Ind. P&S#232BAU12W



### General Information

|                       |                                                                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 232BAU12W                                                                                                                                                          |
| Product ID            | 2CMA166634R1000                                                                                                                                                    |
| EAN                   | 7392696666343                                                                                                                                                      |
| Catalog Description   | Ind. P&S#232BAU12W                                                                                                                                                 |
| Long Description      | Inlet Panel Mounting, unified flange, angled, earthing sleeve position 12h, rated current 32A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Grey |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2417384             |
| E-Number (Finland)     | 2417384             |
| E-Number (Norway)      | 2417384             |
| EAN                    | 7392696666343       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 94 mm  |
| Product Net Height | 101 mm |

|                    |          |
|--------------------|----------|
| Product Net Weight | 0.258 kg |
|--------------------|----------|

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 112 mm                  |
| Package Level 1 Depth / Length | 112 mm                  |
| Package Level 1 Height         | 139 mm                  |
| Package Level 1 Gross Weight   | 0.303 kg                |
| Package Level 1 EAN            | 7392696666343           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 126.05 kg               |
| Package Level 2 EAN            | 7392696069557           |
| Package Level 2 Units          | pallet (lift) 350 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660162X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 2CHC660162X0201 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                               |
|------------------------|-----------------------------------------------|
| Additional Information | 2P+E                                          |
| Ambient Temperature    | -25 ... 40 °C                                 |
| Cable Cross-Section    | 2.5 ... 10 mm²                                |
| Cable Diameter         | 13 ... 21.5 mm                                |
| Color                  | Grey                                          |
| Connection Type        | Screw                                         |
| Degree of Protection   | IP67<br>IP69                                  |
| Design                 | Surface mounted plug                          |
| Frequency (f)          | 60 Hz                                         |
| Function               | Inlet, panel mounting, unified flange, angled |

|                            |                                  |
|----------------------------|----------------------------------|
| Housing Material           | Thermoplastic (PBT)              |
| Invoice Description        | Ind. P&S#232BAU12W               |
| Mounting Holes             | 79,5x79,5                        |
| Mounting Type              | unified flange, angled           |
| Number of Poles            | 3                                |
| Order Multiple             | 1 piece                          |
| Product Main Type          | TBAU                             |
| Product Name               | Panel mounted inlet              |
| Protection Type            | Watertight                       |
| Rated Current ( $I_n$ )    | 32 A                             |
| Rated Frequency (f)        | 60...60 Hz                       |
| Rated Voltage ( $U_r$ )    | Isol. Transformer V              |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Inlets for Panel Mounting        |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 7001 - Silver Grey           |

## Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

## Technical

|                   |                   |
|-------------------|-------------------|
| Wire Size         | 12 ... 10 AWG     |
| Tightening Torque | WireClamp 1.2 N·m |

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

