

PRODUCT-DETAILS

332BAU10W

Ind. P&S#332BAU10W



General Information

Extended Product Type	332BAU10W
Product ID	2CMA166652R1000
EAN	7392696666527
Catalog Description	Ind. P&S#332BAU10W
Long Description	Inlet Panel Mounting, unified flange, angled, earthing sleeve position 10h, rated current 32A, IP67 watertight, 3-poles+earth, frequency 100-300 Hz, color code Green

Ordering

E-Number (Sweden)	2417393
E-Number (Finland)	2417393
E-Number (Norway)	2417393
EAN	7392696666527
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	94 mm
Product Net Height	101 mm

Product Net Weight	0.272 kg
--------------------	----------

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.321 kg
Package Level 1 EAN	7392696666527
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	132.35 kg
Package Level 2 EAN	7392696069649
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660162X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660162X0201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	13 ... 21.5 mm
Color	Green
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	100 ... 300 Hz
Function	Inlet, panel mounting, unified flange, angled

Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#332BAU10W
Mounting Holes	79,5x79,5
Mounting Type	unified flange, angled
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TBAU
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	32 A
Rated Frequency (f)	100...300 Hz
Rated Voltage (U_r)	50 ... 600 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

