

## PRODUCT-DETAILS

# 332P5W

## Ind. P&S#332P5W



### General Information

|                       |                                                                                                                            |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 332P5W                                                                                                                     |
| Product ID            | 2CMA166736R1000                                                                                                            |
| EAN                   | 7392696667364                                                                                                              |
| Catalog Description   | Ind. P&S#332P5W                                                                                                            |
| Long Description      | Plug, earthing sleeve position 5h, rated current 32A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Black |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416267            |
| E-Number (Finland)     | 2421643             |
| E-Number (Norway)      | 2416267             |
| EAN                    | 7392696667364       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |       |
|--------------------|-------|
| Product Net Width  | 94 mm |
| Product Net Height | 94 mm |

|                    |        |
|--------------------|--------|
| Product Net Weight | 0.3 kg |
|--------------------|--------|

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 95 mm                   |
| Package Level 1 Depth / Length | 95 mm                   |
| Package Level 1 Height         | 175 mm                  |
| Package Level 1 Gross Weight   | 0.4 kg                  |
| Package Level 1 EAN            | 7392696667364           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 180 kg                  |
| Package Level 2 EAN            | 7392696070058           |
| Package Level 2 Units          | pallet (lift) 400 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                               |
|------------------------|-------------------------------|
| Additional Information | 3P+E                          |
| Ambient Temperature    | -25 ... 40 °C                 |
| Cable Cross-Section    | 2.5 ... 6 mm²                 |
| Cable Diameter         | 13 ... 21.5 mm                |
| Cable Entry Position   | Cable entry compression gland |
| Color                  | Black                         |
| Connection Type        | Screw                         |
| Degree of Protection   | IP67<br>IP69                  |
| Frequency (f)          | 50 Hz<br>60 Hz                |
| Function               | Plug                          |
| Housing Material       | Thermoplastic (PBT)           |
| Invoice Description    | Ind. P&S#332P5W               |

|                            |                                  |
|----------------------------|----------------------------------|
| Number of Poles            | 4                                |
| Order Multiple             | 1 piece                          |
| Product Main Type          | TP                               |
| Product Name               | Industrial Plug                  |
| Protection Type            | Watertight                       |
| Rated Current ( $I_n$ )    | 32 A                             |
| Rated Voltage ( $U_r$ )    | 600 ... 690 V                    |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Plugs                            |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 7001 - Silver Grey           |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

---

## Technical

|                   |                   |
|-------------------|-------------------|
| Wire Size         | 12 ... 10 AWG     |
| Tightening Torque | WireClamp 1.2 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Plugs

