

PRODUCT-DETAILS

463P4W

Ind. P&S#463P4W



General Information

| | |
|-----------------------|---|
| Extended Product Type | 463P4W |
| Product ID | 2CMA166796R1000 |
| EAN | 7392696667968 |
| Catalog Description | Ind. P&S#463P4W |
| Long Description | Plug, earthing sleeve position 4h, rated current 63A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Yellow |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | 2416293 |
| E-Number (Finland) | 2416293 |
| E-Number (Norway) | 2416293 |
| EAN | 7392696667968 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 114 mm |
| Product Net Height | 114 mm |

| | |
|---------------------|-----------------|
| Product Net Weight | 1.15 kg |
| Mechanical Drawings | 9AKK107492A4181 |

Container Information

| | |
|--------------------------------|-------------------------|
| Package Level 1 Width | 120 mm |
| Package Level 1 Depth / Length | 138 mm |
| Package Level 1 Height | 285 mm |
| Package Level 1 Gross Weight | 1.24 kg |
| Package Level 1 EAN | 7392696667968 |
| Package Level 1 Units | box 1 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 168.8 kg |
| Package Level 2 EAN | 7392696070188 |
| Package Level 2 Units | pallet (lift) 120 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|---|
| Additional Information | 3P+N+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 4 ... 16 mm ² |
| Cable Diameter | 17 ... 35 mm |
| Cable Entry Position | Cable entry, compression gland, internal and external cable clamp |
| Color | Yellow |
| Connection Type | Screw |
| Degree of Protection | IP67 IP69 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Plug |
| Housing Material | Thermoplastic (PBT) |

| | |
|----------------------------|----------------------------------|
| Invoice Description | Ind. P&S#463P4W |
| Number of Poles | 5 |
| Order Multiple | 1 piece |
| Product Main Type | TP |
| Product Name | Industrial Plug |
| Protection Type | Watertight |
| Rated Current (I_n) | 63 A |
| Rated Voltage (U_r) | 57/100 ... 75/130 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2 |
| Suitable For | Plugs |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC000040M0001 |
| Installation Manual | 2CMC000040M0001 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 8 ... 4 AWG |
| Tightening Torque | WireClamp3.5 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Plugs

