

PRODUCT-DETAILS

2125C1W

Ind. P&S#2125C1W



General Information

Extended Product Type	2125C1W
Product ID	2CMA166920R1000
EAN	7392696669207
Catalog Description	Ind. P&S#2125C1W
Long Description	Connector, earthing sleeve position 1h, rated current 125A, IP67 watertight, 2-poles+earth, color code Grey

Ordering

E-Number (Sweden)	2416425
E-Number (Finland)	2416425
E-Number (Norway)	2416425
EAN	7392696669207
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	119 mm
Product Net Height	123 mm

Product Net Weight	1.39 kg
Mechanical Drawings	9AKK107492A4189

Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	1.5 kg
Package Level 1 EAN	7392696669207
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	119 kg
Package Level 2 EAN	7392696070591
Package Level 2 Units	pallet (lift) 66 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 50 mm ²
Cable Diameter	24 ... 48 mm
Cable Entry Position	Anti-kink sleeve
Color	Grey
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	AC Hz
Function	Connector
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#2125C1W
Number of Poles	3
Order Multiple	1 piece
Product Main Type	TC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I_n)	125 A
Rated Voltage (U_r)	Optional voltage V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Connectors
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	3 ... 1 AWG
Tightening Torque	WireClamp5.6 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

