

## PRODUCT-DETAILS

# 332RAU6W

## Ind. P&S#332RAU6W



### General Information

|                       |                                                                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 332RAU6W                                                                                                                                                                  |
| Product ID            | 2CMA166964R1000                                                                                                                                                           |
| EAN                   | 7392696669641                                                                                                                                                             |
| Catalog Description   | Ind. P&S#332RAU6W                                                                                                                                                         |
| Long Description      | Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 32A, IP67 watertight, unified flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Red |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416726            |
| E-Number (Finland)     | 2421274             |
| E-Number (Norway)      | 1561943             |
| EAN                    | 7392696669641       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 95 mm           |
| Product Net Height  | 117 mm          |
| Product Net Weight  | 0.21 kg         |
| Mechanical Drawings | 9AKK107991A3794 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 112 mm                  |
| Package Level 1 Depth / Length | 112 mm                  |
| Package Level 1 Height         | 139 mm                  |
| Package Level 1 Gross Weight   | 0.3 kg                  |
| Package Level 1 EAN            | 7392696669641           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 125 kg                  |
| Package Level 2 EAN            | 7392696070812           |
| Package Level 2 Units          | pallet (lift) 350 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1613211         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                                       |
|------------------------|-------------------------------------------------------|
| Additional Information | 3P+E                                                  |
| Ambient Temperature    | -25 ... 40 °C                                         |
| Cable Cross-Section    | 2.5 ... 10 mm²                                        |
| Cable Diameter         | 13 ... 21.5 mm                                        |
| Color                  | Red                                                   |
| Connection Type        | Screw                                                 |
| Degree of Protection   | IP67<br>IP69                                          |
| Frequency (f)          | 50 Hz<br>60 Hz                                        |
| Function               | Socket outlet, panel mounting, unified flange, angled |
| Housing Material       | Thermoplastic (PBT)                                   |
| Invoice Description    | Ind. P&S#332RAU6W                                     |
| Mounting Holes         | 79.5x79.5                                             |
| Mounting Type          | unified flange, angled                                |
| Number of Poles        | 4                                                     |
| Order Multiple         | 1 piece                                               |
| Product Main Type      | TRAU                                                  |
| Product Name           | Panel mounted socket                                  |

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Protection Type                 | Watertight                        |
| Rated Current (I <sub>n</sub> ) | 32 A                              |
| Rated Frequency (f)             | 50...60 Hz                        |
| Rated Voltage (U <sub>r</sub> ) | 380 ... 415 V                     |
| Recommended Screw Driver        | PH2                               |
| Standards                       | IEC 60309-1, -2                   |
| Suitable For                    | Socket Outlets for Panel Mounting |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets  |
| Instructions and Manuals        | 2CMC700014C0016                   |
| RAL Number                      | RAL 7001 - Silver Grey            |

Classifications

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

