

PRODUCT-DETAILS

432RAU2W

Ind. P&S#432RAU2W



General Information

Extended Product Type	432RAU2W
Product ID	2CMA166976R1000
EAN	7392696669764
Catalog Description	Ind. P&S#432RAU2W
Long Description	Socket-outlet, panel mounting, earthing sleeve position 2h, rated current 32A, IP67 watertight, unified flange, angled, 3-poles+neutral+earth, frequency 300-500 Hz, color code Green

Ordering

E-Number (Sweden)	2416732
E-Number (Finland)	2416732
E-Number (Norway)	2416732
EAN	7392696669764
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	99 mm
Product Net Height	118 mm
Product Net Weight	0.32 kg

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.37 kg
Package Level 1 EAN	7392696669764
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	149.5 kg
Package Level 2 EAN	7392696071444
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	13 ... 21.5 mm
Color	Green
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	>300 ... 500 Hz
Function	Socket outlet, panel mounting, unified flange, angled
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#432RAU2W
Mounting Holes	79.5x79.5
Mounting Type	unified flange, angled
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRAU
Product Name	Panel mounted socket
Protection Type	Watertight

Rated Current (I _n)	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	50 ... 500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

