

PRODUCT-DETAILS

416RAU9W

Ind. P&S#416RAU9W



General Information

| | |
|-----------------------|--|
| Extended Product Type | 416RAU9W |
| Product ID | 2CMA167034R1000 |
| EAN | 7392696670340 |
| Catalog Description | Ind. P&S#416RAU9W |
| Long Description | Socket-outlet, panel mounting, earthing sleeve position 9h, rated current 16A, IP67 watertight, unified flange, angled, 3-poles+neutral+earth, frequency 50-60 Hz, color code Blue |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | 2416714 |
| E-Number (Finland) | 2416714 |
| E-Number (Norway) | 2416714 |
| EAN | 7392696670340 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|---------|
| Product Net Width | 104 mm |
| Product Net Height | 104 mm |
| Product Net Weight | 0.18 kg |

Container Information

| | |
|--------------------------------|-------------------------|
| Package Level 1 Width | 110 mm |
| Package Level 1 Depth / Length | 110 mm |
| Package Level 1 Height | 110 mm |
| Package Level 1 Gross Weight | 0.18 kg |
| Package Level 1 EAN | 7392696670340 |
| Package Level 1 Units | box 1 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 95.6 kg |
| Package Level 2 EAN | 7392696070881 |
| Package Level 2 Units | pallet (lift) 420 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1613211 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|---|
| Additional Information | 3P+N+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 1.5 ... 4 mm ² |
| Cable Diameter | 13 ... 17 mm |
| Color | Blue |
| Connection Type | Screw |
| Degree of Protection | IP67 IP69 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Socket outlet, panel mounting, unified flange, angled |
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | Ind. P&S#416RAU9W |
| Mounting Holes | 79.5x79.5 |
| Mounting Type | unified flange, angled |
| Number of Poles | 5 |
| Order Multiple | 1 piece |
| Product Main Type | TRAU |
| Product Name | Panel mounted socket |

| | |
|----------------------------|-----------------------------------|
| Protection Type | Watertight |
| Rated Current (I_n) | 16 A |
| Rated Frequency (f) | 50...60 Hz |
| Rated Voltage (U_r) | 120/208 ... 144/250 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2 |
| Suitable For | Socket Outlets for Panel Mounting |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC700014C0016 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 14 ... 12 AWG |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

