

PRODUCT-DETAILS

# 4125RU1W

## Ind. P&S#4125RU1W



### General Information

Extended Product Type	4125RU1W
Product ID	2CMA167146R1000
EAN	7392696671460
Catalog Description	Ind. P&S#4125RU1W
Long Description	Socket-outlet, panel mounting, earthing sleeve position 1h, rated current 125A, IP67 watertight, unified flange, straight, 3-poles+neutral+earth

### Ordering

E-Number (Sweden)	2416788
E-Number (Finland)	2416788
E-Number (Norway)	2416788
EAN	7392696671460
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

### Dimensions

Product Net Width	115 mm
Product Net Height	158 mm
Product Net Weight	1.14 kg
Mechanical Drawings	9AKK107991A3871

---

**Container Information**


---

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	1.14 kg
Package Level 1 EAN	7392696671460
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	218.36 kg
Package Level 2 EAN	7392696071802
Package Level 2 Units	pallet (lift) 174 piece

---



---

**Environmental**


---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---



---

**Certificates and Declarations (Document Number)**


---

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614199
REACH Declaration	2CMC700005D0001

---



---

**Additional Information**


---

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 70 mm <sup>2</sup>
Color	Grey
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	AC Hz
Function	Socket outlet, panel mounting, unified flange, straight
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#4125RU1W
Mounting Holes	71x71
Mounting Type	unified flange, straight
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	125 A

Rated Frequency (f)	50...60 Hz
Rated Voltage (U <sub>r</sub> )	Optional voltage V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

## Classifications

eClass	27440504
UNSPSC	39120000

## Technical

Tightening Torque	WireClamp5.6 N·m
-------------------	------------------

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

