
PRODUCT-DETAILS

316RS10W

Ind. P&S#316RS10W



General Information

| | |
|-----------------------|--|
| Extended Product Type | 316RS10W |
| Product ID | 2CMA167160R1000 |
| EAN | 7392696671606 |
| Catalog Description | Ind. P&S#316RS10W |
| Long Description | Surface socket-outlet, earthing sleeve position 10h, rated current 16A, IP67 watertight, 3-poles+earth, frequency 100-300 Hz, color code Green |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | 2416535 |
| E-Number (Finland) | 2416535 |
| E-Number (Norway) | 2416535 |
| EAN | 7392696671606 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 99 mm |
| Product Net Height | 170 mm |

| | |
|---------------------|-----------------|
| Product Net Weight | 0.37 kg |
| Mechanical Drawings | 9AKK107991A3822 |

Container Information

| | |
|--------------------------------|-------------------------|
| Package Level 1 Width | 135 mm |
| Package Level 1 Depth / Length | 140 mm |
| Package Level 1 Height | 200 mm |
| Package Level 1 Gross Weight | 0.37 kg |
| Package Level 1 EAN | 7392696671606 |
| Package Level 1 Units | box 1 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 84.38 kg |
| Package Level 2 EAN | 7392696071932 |
| Package Level 2 Units | pallet (lift) 174 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1613211 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|---------------------------|
| Additional Information | 3P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 1.5 ... 4 mm ² |
| Cable Diameter | 25 mm |
| Cable Entry Position | Cable entry Ø 25mm |
| Color | Green |
| Connection Type | Screw |
| Degree of Protection | IP67 IP69 |
| Frequency (f) | 100 ... 300 Hz |
| Function | Surface socket outlet |

| | |
|----------------------------|----------------------------------|
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | Ind. P&S#316RS10W |
| Mounting Holes | 60x148,2 |
| Number of Poles | 4 |
| Order Multiple | 1 piece |
| Product Main Type | TRS |
| Product Name | Wall mounted socket |
| Protection Type | Watertight |
| Rated Current (I_n) | 16 A |
| Rated Voltage (U_r) | 50 ... 600 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2 |
| Suitable For | Surface Socket Outlets |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC700014C0016 |
| Installation Manual | 2CMC700014C0016 |
| RAL Number | RAL 7012 - Basalt Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 14 ... 12 AWG |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

