

## PRODUCT-DETAILS

# 316RS11W

## Ind. P&S#316RS11W



### General Information

|                       |                                                                                                                                         |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 316RS11W                                                                                                                                |
| Product ID            | 2CMA167161R1000                                                                                                                         |
| EAN                   | 7392696671613                                                                                                                           |
| Catalog Description   | Ind. P&S#316RS11W                                                                                                                       |
| Long Description      | Surface socket-outlet, earthing sleeve position 11h, rated current 16A, IP67 watertight, 3-poles+earth, frequency 60 Hz, color code Red |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2416536             |
| E-Number (Finland)     | 2416536             |
| E-Number (Norway)      | 2416536             |
| EAN                    | 7392696671613       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 99 mm           |
| Product Net Height  | 170 mm          |
| Product Net Weight  | 0.37 kg         |
| Mechanical Drawings | 9AKK107991A3822 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 135 mm                  |
| Package Level 1 Depth / Length | 140 mm                  |
| Package Level 1 Height         | 200 mm                  |
| Package Level 1 Gross Weight   | 0.37 kg                 |
| Package Level 1 EAN            | 7392696671613           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 84.38 kg                |
| Package Level 2 EAN            | 7392696071949           |
| Package Level 2 Units          | pallet (lift) 174 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1613211         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                           |
|------------------------|---------------------------|
| Additional Information | 3P+E                      |
| Ambient Temperature    | -25 ... 40 °C             |
| Cable Cross-Section    | 1.5 ... 4 mm <sup>2</sup> |
| Cable Diameter         | 25 mm                     |
| Cable Entry Position   | Cable entry Ø 25mm        |
| Color                  | Red                       |
| Connection Type        | Screw                     |
| Degree of Protection   | IP67<br>IP69              |
| Frequency (f)          | 60 Hz                     |
| Function               | Surface socket outlet     |
| Housing Material       | Thermoplastic (PBT)       |
| Invoice Description    | Ind. P&S#316RS11W         |
| Mounting Holes         | 60x148,2                  |
| Number of Poles        | 4                         |
| Order Multiple         | 1 piece                   |
| Product Main Type      | TRS                       |
| Product Name           | Wall mounted socket       |
| Protection Type        | Watertight                |

|                            |                                  |
|----------------------------|----------------------------------|
| Rated Current ( $I_n$ )    | 16 A                             |
| Rated Voltage ( $U_r$ )    | 440 ... 460 V                    |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Surface Socket Outlets           |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| Installation Manual        | 2CMC700014C0016                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

