

PRODUCT-DETAILS

# 416RS2W

## Ind. P&S#416RS2W



### General Information

Extended Product Type	416RS2W
Product ID	2CMA167163R1000
EAN	7392696671637
Catalog Description	Ind. P&S#416RS2W
Long Description	Surface socket-outlet, earthing sleeve position 2h, rated current 16A, IP67 watertight, 3-poles+neutral+earth, frequency >300-500 Hz, color code Green

### Ordering

E-Number (Sweden)	2416538
E-Number (Finland)	2416538
E-Number (Norway)	2416538
EAN	7392696671637
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

### Dimensions

Product Net Width	124 mm
Product Net Height	99 mm
Product Net Weight	0.40 kg
Mechanical Drawings	9AKK107991A3846

---

**Container Information**


---

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	0.4 kg
Package Level 1 EAN	7392696671637
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	89.6 kg
Package Level 2 EAN	7392696071963
Package Level 2 Units	pallet (lift) 174 piece

---



---

**Environmental**


---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---



---

**Certificates and Declarations (Document Number)**


---

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

---



---

**Additional Information**


---

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm <sup>2</sup>
Cable Diameter	25 mm
Cable Entry Position	Cable entry Ø 25mm
Color	Green
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	>300 ... 500 Hz
Function	Surface socket outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#416RS2W
Mounting Holes	60x148,2
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Watertight

Rated Current ( $I_n$ )	16 A
Rated Voltage ( $U_r$ )	50 ... 500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

## Classifications

eClass	27440510
UNSPSC	39120000

## Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

