

PRODUCT-DETAILS

4125BU4W

Ind. P&S#4125BU4W



General Information

Extended Product Type	4125BU4W
Product ID	2CMA167203R1000
EAN	7392696672030
Catalog Description	Ind. P&S#4125BU4W
Long Description	Inlet, panel mounting, earthing sleeve position 4h, rated current 125A, IP67 watertight, unified flange, straight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Yellow

Ordering

E-Number (Sweden)	2417430
E-Number (Finland)	2417430
E-Number (Norway)	2417430
EAN	7392696672030
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	127 mm
Product Net Height	127 mm

Product Net Weight	1 kg
--------------------	------

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	1.1 kg
Package Level 1 EAN	7392696672030
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	211.4 kg
Package Level 2 EAN	7392696072366
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614197
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 70 mm ²
Color	Yellow
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet, panel mounting, unified flange, straight
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#4125BU4W

Mounting Holes	71x71
Mounting Type	unified flange, straight
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TBU
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	125 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	57/100 ... 75/130 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

