

PRODUCT-DETAILS

# 3125BS4W

## Ind. P&S#3125BS4W



### General Information

Extended Product Type	3125BS4W
Product ID	2CMA167280R1000
EAN	7392696672801
Catalog Description	Ind. P&S#3125BS4W
Long Description	Surface Inlet, earthing sleeve position 4h, rated current 125A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Yellow

### Ordering

E-Number (Sweden)	2417278
E-Number (Finland)	2420199
E-Number (Norway)	2417278
EAN	7392696672801
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

### Dimensions

Product Net Width	145 mm
Product Net Height	161 mm

Product Net Weight	4.1 kg
--------------------	--------

## Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	4.1 kg
Package Level 1 EAN	7392696672801
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	204.5 kg
Package Level 2 EAN	7392696072700
Package Level 2 Units	pallet (lift) 45 piece

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614197
REACH Declaration	2CMC700005D0001

## Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 70 mm <sup>2</sup>
Cable Entry Position	Cable entry Ø50mm
Color	Yellow
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Surface inlet
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#3125BS4W
Mounting Holes	188x85
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TBS
Product Name	Wall mounted inlet
Protection Type	Watertight
Rated Current ( $I_n$ )	125 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	100 ... 130 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Inlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7012 - Basalt Grey

---

## Classifications

eClass	27440519
UNSPSC	39120000

---

## Technical

Wire Size	3 ... 1 AWG
Tightening Torque	WireClamp5.6 N·m

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Inlets

