

## PRODUCT-DETAILS

# 3125BS9W

## Ind. P&S#3125BS9W



### General Information

|                       |                                                                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 3125BS9W                                                                                                                            |
| Product ID            | 2CMA167286R1000                                                                                                                     |
| EAN                   | 7392696672863                                                                                                                       |
| Catalog Description   | Ind. P&S#3125BS9W                                                                                                                   |
| Long Description      | Surface Inlet, earthing sleeve position 9h, rated current 125A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Blue |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2417281             |
| E-Number (Finland)     | 2417281             |
| E-Number (Norway)      | 2417281             |
| EAN                    | 7392696672863       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 145 mm |
| Product Net Height | 161 mm |
| Product Net Weight | 4.1 kg |

## Container Information

|                                |                        |
|--------------------------------|------------------------|
| Package Level 1 Width          | 154 mm                 |
| Package Level 1 Depth / Length | 182 mm                 |
| Package Level 1 Height         | 378 mm                 |
| Package Level 1 Gross Weight   | 4.1 kg                 |
| Package Level 1 EAN            | 7392696672863          |
| Package Level 1 Units          | box 1 piece            |
| Package Level 2 Width          | 800 mm                 |
| Package Level 2 Depth / Length | 1200 mm                |
| Package Level 2 Height         | 900 mm                 |
| Package Level 2 Gross Weight   | 204.5 kg               |
| Package Level 2 EAN            | 7392696072731          |
| Package Level 2 Units          | pallet (lift) 45 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1614197         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                      |
|------------------------|----------------------|
| Additional Information | 3P+E                 |
| Ambient Temperature    | -25 ... 40 °C        |
| Cable Cross-Section    | 16 ... 70 mm²        |
| Cable Entry Position   | Cable entry Ø50mm    |
| Color                  | Blue                 |
| Connection Type        | Screw                |
| Degree of Protection   | IP67<br>IP69         |
| Design                 | Surface mounted plug |
| Frequency (f)          | 50 Hz<br>60 Hz       |
| Function               | Surface inlet        |
| Housing Material       | Thermoplastic (PBT)  |
| Invoice Description    | Ind. P&S#3125BS9W    |
| Mounting Holes         | 188x85               |
| Number of Poles        | 4                    |
| Order Multiple         | 1 piece              |
| Product Main Type      | TBS                  |
| Product Name           | Wall mounted inlet   |
| Protection Type        | Watertight           |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Rated Current (I <sub>n</sub> ) | 125 A                            |
| Rated Frequency (f)             | 50...60 Hz                       |
| Rated Voltage (U <sub>r</sub> ) | 200 ... 250 V                    |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2                  |
| Suitable For                    | Surface Inlets                   |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC000040M0001                  |
| Installation Manual             | 2CMC000040M0001                  |
| RAL Number                      | RAL 7012 - Basalt Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 3 ... 1 AWG      |
| Tightening Torque | WireClamp5.6 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Inlets

