

---

PRODUCT-DETAILS

# 263RS9W

## Ind. P&S#263RS9W




---

### General Information

Extended Product Type	263RS9W
Product ID	2CMA167308R1000
EAN	7392696673082
Catalog Description	Ind. P&S#263RS9W
Long Description	Surface socket-outlet, earthing sleeve position 9h, rated current 63A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Red

---

### Ordering

E-Number (Sweden)	2416571
E-Number (Finland)	2421838
E-Number (Norway)	2416571
EAN	7392696673082
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

---

### Dimensions

Product Net Width	118 mm
Product Net Height	263 mm

Product Net Weight	1 kg
Mechanical Drawings	9AKK107991A3820

---

## Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	1.11 kg
Package Level 1 EAN	7392696673082
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	158.75 kg
Package Level 2 EAN	7392696072854
Package Level 2 Units	pallet (lift) 125 piece

---

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

---

## Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm <sup>2</sup>
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#263RS9W
Mounting Holes	176x76

Number of Poles	3
Order Multiple	1 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current ( $I_n$ )	63 A
Rated Voltage ( $U_r$ )	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7012 - Basalt Grey

## Classifications

eClass	27440510
UNSPSC	39120000

## Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

