

## PRODUCT-DETAILS

# 463RS11W

## Ind. P&S#463RS11W



### General Information

|                       |                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 463RS11W                                                                                                                                        |
| Product ID            | 2CMA167334R1000                                                                                                                                 |
| EAN                   | 7392696673341                                                                                                                                   |
| Catalog Description   | Ind. P&S#463RS11W                                                                                                                               |
| Long Description      | Surface socket-outlet, earthing sleeve position 11h, rated current 63A, IP67 watertight, 3-poles+neutral+earth, frequency 60 Hz, color code Red |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416584            |
| E-Number (Finland)     | 2416584             |
| E-Number (Norway)      | 2416584             |
| EAN                    | 7392696673341       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 118 mm |
| Product Net Height | 263 mm |

|                     |                 |
|---------------------|-----------------|
| Product Net Weight  | 1.15 kg         |
| Mechanical Drawings | 9AKK107991A3848 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 1.26 kg                 |
| Package Level 1 EAN            | 7392696673341           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 177.5 kg                |
| Package Level 2 EAN            | 7392696072984           |
| Package Level 2 Units          | pallet (lift) 125 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                          |
|------------------------|--------------------------|
| Additional Information | 3P+N+E                   |
| Ambient Temperature    | -25 ... 40 °C            |
| Cable Cross-Section    | 6 ... 25 mm <sup>2</sup> |
| Color                  | Red                      |
| Connection Type        | Screw                    |
| Degree of Protection   | IP67<br>IP69             |
| Frequency (f)          | 60 Hz                    |
| Function               | Surface socket outlet    |
| Housing Material       | Thermoplastic (PBT)      |
| Invoice Description    | Ind. P&S#463RS11W        |
| Mounting Holes         | 176x76                   |

|                            |                                  |
|----------------------------|----------------------------------|
| Number of Poles            | 5                                |
| Order Multiple             | 1 piece                          |
| Product Main Type          | TRS                              |
| Product Name               | Wall mounted socket              |
| Protection Type            | Watertight                       |
| Rated Current ( $I_n$ )    | 63 A                             |
| Rated Voltage ( $U_r$ )    | 250/440 ... 265/460 V            |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Surface Socket Outlets           |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC000038M0001                  |
| Installation Manual        | 2CMC000038M0001                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

