

---

PRODUCT-DETAILS

# 463BS9W

## Ind. P&S#463BS9W




---

### General Information

Extended Product Type	463BS9W
Product ID	2CMA167366R1000
EAN	7392696673662
Catalog Description	Ind. P&S#463BS9W
Long Description	Surface Inlet, earthing sleeve position 9h, rated current 63A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Blue

---

### Ordering

E-Number (Sweden)	2417272
E-Number (Finland)	2417272
E-Number (Norway)	2417272
EAN	7392696673662
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

---

### Dimensions

Product Net Width	118 mm
Product Net Height	140 mm

Product Net Weight	0.99 kg
Mechanical Drawings	9AKK107680A0026

---

## Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	1.1 kg
Package Level 1 EAN	7392696673662
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	157.5 kg
Package Level 2 EAN	7392696073424
Package Level 2 Units	pallet (lift) 125 piece

---

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

## Certificates and Declarations (Document Number)

CB Certificate	2CHC660163X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

---

## Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm <sup>2</sup>
Cable Entry Position	Cable entry Ø32mm
Color	Blue
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz

Function	Surface inlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463BS9W
Mounting Holes	176x76
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TBS
Product Name	Wall mounted inlet
Protection Type	Watertight
Rated Current ( $I_n$ )	63 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	120/208 ... 144/250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Inlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7012 - Basalt Grey

## Classifications

eClass	27440519
UNSPSC	39120000

## Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Inlets

