

## PRODUCT-DETAILS

# 363RU5W

## Ind. P&S#363RU5W



### General Information

|                       |                                                                                                                                                                               |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 363RU5W                                                                                                                                                                       |
| Product ID            | 2CMA167382R1000                                                                                                                                                               |
| EAN                   | 7392696673822                                                                                                                                                                 |
| Catalog Description   | Ind. P&S#363RU5W                                                                                                                                                              |
| Long Description      | Socket-outlet, panel mounting, earthing sleeve position 5h, rated current 63A, IP67 watertight, unified flange, straight, 3-poles+earth, frequency 50-60 Hz, color code Black |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2416745             |
| E-Number (Finland)     | 2409546             |
| E-Number (Norway)      | 2416745             |
| EAN                    | 7392696673822       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 107 mm |
| Product Net Height | 137 mm |

|                     |                 |
|---------------------|-----------------|
| Product Net Weight  | 0.6 kg          |
| Mechanical Drawings | 9AKK107991A3866 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 112 mm                  |
| Package Level 1 Depth / Length | 112 mm                  |
| Package Level 1 Height         | 139 mm                  |
| Package Level 1 Gross Weight   | 0.65 kg                 |
| Package Level 1 EAN            | 7392696673822           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 247.5 kg                |
| Package Level 2 EAN            | 7392696073509           |
| Package Level 2 Units          | pallet (lift) 350 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1614199         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                                         |
|------------------------|---------------------------------------------------------|
| Additional Information | 3P+E                                                    |
| Ambient Temperature    | -25 ... 40 °C                                           |
| Cable Cross-Section    | 6 ... 25 mm²                                            |
| Color                  | Black                                                   |
| Connection Type        | Screw                                                   |
| Degree of Protection   | IP67<br>IP69                                            |
| Frequency (f)          | 50 Hz<br>60 Hz                                          |
| Function               | Socket outlet, panel mounting, unified flange, straight |
| Housing Material       | Thermoplastic (PBT)                                     |
| Invoice Description    | Ind. P&S#363RU5W                                        |

|                            |                                   |
|----------------------------|-----------------------------------|
| Mounting Holes             | 61x61                             |
| Mounting Type              | unified flange, straight          |
| Number of Poles            | 4                                 |
| Order Multiple             | 1 piece                           |
| Product Main Type          | TRU                               |
| Product Name               | Panel mounted socket              |
| Protection Type            | Watertight                        |
| Rated Current ( $I_n$ )    | 63 A                              |
| Rated Frequency (f)        | 50...60 Hz                        |
| Rated Voltage ( $U_r$ )    | 600 ... 690 V                     |
| Recommended Screw Driver   | PH2                               |
| Standards                  | IEC 60309-1, -2                   |
| Suitable For               | Socket Outlets for Panel Mounting |
| Suitable for Product Class | IEC Industrial Plugs and Sockets  |
| Instructions and Manuals   | 2CMC000038M0001                   |
| Installation Manual        | 2CMC000038M0001                   |
| RAL Number                 | RAL 7001 - Silver Grey            |

Classifications

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Tightening Torque | WireClamp3.5 N·m |
|-------------------|------------------|

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

