


PRODUCT-DETAILS

463RU4W

Ind. P&S#463RU4W



General Information

Extended Product Type	463RU4W
Product ID	2CMA167394R1000
EAN	7392696673945
Catalog Description	Ind. P&S#463RU4W
Long Description	Socket-outlet, panel mounting, earthing sleeve position 4h, rated current 63A, IP67 watertight, unified flange, straight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Yellow

Ordering

E-Number (Sweden)	2416751
E-Number (Finland)	2416751
E-Number (Norway)	2416751
EAN	7392696673945
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	107 mm
Product Net Height	137 mm
Product Net Weight	0.76 kg
Mechanical Drawings	9AKK107991A3867

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.76 kg
Package Level 1 EAN	7392696673945
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	286 kg
Package Level 2 EAN	7392696073561
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614199
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Color	Yellow
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet, panel mounting, unified flange, straight
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463RU4W
Mounting Holes	61x61
Mounting Type	unified flange, straight
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRU
Product Name	Panel mounted socket

Protection Type	Watertight
Rated Current (I_n)	63 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	57/100 ... 75/130 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Tightening Torque	WireClamp3.5 N·m
-------------------	------------------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

