


## PRODUCT-DETAILS

# 363RAU6W

## Ind. P&S#363RAU6W



### General Information

|                       |                                                                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 363RAU6W                                                                                                                                                                  |
| Product ID            | 2CMA167452R1000                                                                                                                                                           |
| EAN                   | 7392696674522                                                                                                                                                             |
| Catalog Description   | Ind. P&S#363RAU6W                                                                                                                                                         |
| Long Description      | Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 63A, IP67 watertight, unified flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Red |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416763            |
| E-Number (Finland)     | 2421283             |
| E-Number (Norway)      | 1562073             |
| EAN                    | 7392696674522       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 106 mm          |
| Product Net Height  | 147 mm          |
| Product Net Weight  | 0.63 kg         |
| Mechanical Drawings | 9AKK107991A3796 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 112 mm                  |
| Package Level 1 Depth / Length | 112 mm                  |
| Package Level 1 Height         | 139 mm                  |
| Package Level 1 Gross Weight   | 0.63 kg                 |
| Package Level 1 EAN            | 7392696674522           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 240.5 kg                |
| Package Level 2 EAN            | 7392696073226           |
| Package Level 2 Units          | pallet (lift) 350 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1614204         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                                       |
|------------------------|-------------------------------------------------------|
| Additional Information | 3P+E                                                  |
| Ambient Temperature    | -25 ... 40 °C                                         |
| Cable Cross-Section    | 6 ... 25 mm <sup>2</sup>                              |
| Cable Diameter         | 17 ... 35 mm                                          |
| Color                  | Red                                                   |
| Connection Type        | Screw                                                 |
| Degree of Protection   | IP67<br>IP69                                          |
| Frequency (f)          | 50 Hz<br>60 Hz                                        |
| Function               | Socket outlet, panel mounting, unified flange, angled |
| Housing Material       | Thermoplastic (PBT)                                   |
| Invoice Description    | Ind. P&S#363RAU6W                                     |
| Mounting Holes         | 84x80                                                 |
| Mounting Type          | unified flange, angled                                |
| Number of Poles        | 4                                                     |
| Order Multiple         | 1 piece                                               |
| Product Main Type      | TRAU                                                  |
| Product Name           | Panel mounted socket                                  |

|                            |                                   |
|----------------------------|-----------------------------------|
| Protection Type            | Watertight                        |
| Rated Current ( $I_n$ )    | 63 A                              |
| Rated Frequency (f)        | 50...60 Hz                        |
| Rated Voltage ( $U_r$ )    | 380 ... 415 V                     |
| Recommended Screw Driver   | PH2                               |
| Standards                  | IEC 60309-1, -2                   |
| Suitable For               | Socket Outlets for Panel Mounting |
| Suitable for Product Class | IEC Industrial Plugs and Sockets  |
| Instructions and Manuals   | 2CMC000038M0001                   |
| Installation Manual        | 2CMC000038M0001                   |
| RAL Number                 | RAL 7001 - Silver Grey            |

Classifications

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

