


PRODUCT-DETAILS

363RAU9W

Ind. P&S#363RAU9W



General Information

Extended Product Type	363RAU9W
Product ID	2CMA167456R1000
EAN	7392696674560
Catalog Description	Ind. P&S#363RAU9W
Long Description	Socket-outlet, panel mounting, earthing sleeve position 9h, rated current 63A, IP67 watertight, unified flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Blue

Ordering

E-Number (Sweden)	2416765
E-Number (Finland)	2416765
E-Number (Norway)	2416765
EAN	7392696674560
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	106 mm
Product Net Height	147 mm

Product Net Weight	0.63 kg
--------------------	---------

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.63 kg
Package Level 1 EAN	7392696674560
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	240.5 kg
Package Level 2 EAN	7392696073240
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614204
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm ²
Cable Diameter	17 ... 35 mm
Color	Blue
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet, panel mounting, unified flange, angled
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#363RAU9W

Mounting Holes	84x80
Mounting Type	unified flange, angled
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TRAU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I_n)	63 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

