

PRODUCT-DETAILS

# 363RS5

## Surface socket-outlet, 5h, 63A, IP44, 3P+E



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | 363RS5   |
| Product ID            | 2CMA167496R1000  |
| EAN                   | 7392696674966  |
| Catalog Description   | Surface socket-outlet, 5h, 63A, IP44, 3P+E   |
| Long Description      | Surface socket-outlet, earthing sleeve position 5h, rated current 63A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Black |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2416512             |
| E-Number (Finland)     | 2409516             |
| E-Number (Norway)      | 2416512             |
| EAN                    | 7392696674966       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 107 mm          |
| Product Net Height  | 254 mm          |
| Product Net Weight  | 0.99 kg         |
| Mechanical Drawings | 9AKK107680A0707 |

---

**Container Information**


---

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 1.077 kg                |
| Package Level 1 EAN            | 7392696674966           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 154.625 kg              |
| Package Level 2 EAN            | 7392696073707           |
| Package Level 2 Units          | pallet (lift) 125 piece |

---



---

**Environmental**


---

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

---



---

**Certificates and Declarations (Document Number)**


---

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1614199         |
| REACH Declaration              | 2CMC700005D0001 |

---



---

**Additional Information**


---

|                                 |  |
|---------------------------------|--|
| Additional Information          | 3P+E   |
| Ambient Temperature             | -25 ... 40 °C  |
| Cable Cross-Section             | 6 ... 25 mm <sup>2</sup>                                 |
| Cable Entry Position            | Cable entry, M32, alternative rear knock-out cable entry |
| Color                           | Black  |
| Connection Type                 | Screw  |
| Degree of Protection            | IP44   |
| Frequency (f)                   | 50 Hz<br>60 Hz   |
| Function                        | Surface socket outlet                                    |
| Housing Material                | Thermoplastic (PBT)                                      |
| Invoice Description             | Ind. P&S#363RS5  |
| Mounting Holes                  | 170x95   |
| Number of Poles                 | 4  |
| Order Multiple                  | 1 piece  |
| Product Main Type               | TRS  |
| Product Name                    | Wall mounted socket                                      |
| Protection Type                 | Splashproof  |
| Rated Current (I <sub>n</sub> ) | 63 A   |

|                            |                                  |
|----------------------------|----------------------------------|
| Rated Voltage ( $U_r$ )    | 600 ... 690 V                    |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Surface Socket Outlets           |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC000038M0001                  |
| Installation Manual        | 2CMC000038M0001                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39121406 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

