

## PRODUCT-DETAILS

# 263RU4

## Ind. P&S#263RU4



### General Information

|                       |                                                                                                                                                                                 |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 263RU4                                                                                                                                                                          |
| Product ID            | 2CMA167508R1000                                                                                                                                                                 |
| EAN                   | 7392696675086                                                                                                                                                                   |
| Catalog Description   | Ind. P&S#263RU4                                                                                                                                                                 |
| Long Description      | Socket-outlet, panel mounting, earthing sleeve position 4h, rated current 63A, IP44 splashproof, unified flange, straight, 2-poles+earth, frequency 50-60 Hz, color code Yellow |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2416672             |
| E-Number (Finland)     | 2420128             |
| E-Number (Norway)      | 2416672             |
| EAN                    | 7392696675086       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 98 mm           |
| Product Net Height  | 135 mm          |
| Product Net Weight  | 0.6 kg          |
| Mechanical Drawings | 9AKK107991A3854 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 112 mm                  |
| Package Level 1 Depth / Length | 112 mm                  |
| Package Level 1 Height         | 139 mm                  |
| Package Level 1 Gross Weight   | 0.6 kg                  |
| Package Level 1 EAN            | 7392696675086           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 230 kg                  |
| Package Level 2 EAN            | 7392696073769           |
| Package Level 2 Units          | pallet (lift) 350 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1614199         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                                                         |
|---------------------------------|---------------------------------------------------------|
| Additional Information          | 2P+E                                                    |
| Ambient Temperature             | -25 ... 40 °C                                           |
| Cable Cross-Section             | 6 ... 25 mm <sup>2</sup>                                |
| Color                           | Yellow                                                  |
| Connection Type                 | Screw                                                   |
| Degree of Protection            | IP44                                                    |
| Frequency (f)                   | 50 Hz<br>60 Hz                                          |
| Function                        | Socket outlet, panel mounting, unified flange, straight |
| Housing Material                | Thermoplastic (PBT)                                     |
| Invoice Description             | Ind. P&S#263RU4                                         |
| Mounting Holes                  | 61x61                                                   |
| Mounting Type                   | unified flange, straight                                |
| Number of Poles                 | 3                                                       |
| Order Multiple                  | 1 piece                                                 |
| Product Main Type               | TRU                                                     |
| Product Name                    | Panel mounted socket                                    |
| Protection Type                 | Splashproof                                             |
| Rated Current (I <sub>n</sub> ) | 63 A                                                    |

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Rated Frequency (f)             | 50...60 Hz                        |
| Rated Voltage (U <sub>r</sub> ) | 100 ... 130 V                     |
| Recommended Screw Driver        | PH2                               |
| Standards                       | IEC 60309-1, -2                   |
| Suitable For                    | Socket Outlets for Panel Mounting |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets  |
| Instructions and Manuals        | 2CMC000038M0001                   |
| Installation Manual             | 2CMC000038M0001                   |
| RAL Number                      | RAL 7001 - Silver Grey            |

Classifications

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39121406 |

Technical

|                   |                  |
|-------------------|------------------|
| Tightening Torque | WireClamp3.5 N·m |
|-------------------|------------------|

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

