

PRODUCT-DETAILS

# 363BS7

## Surface inlet, 7h, 63A, IP44, 3P+E



### General Information

Extended Product Type	363BS7
Product ID	2CMA167556R1000
EAN	7392696675567
Catalog Description	Surface inlet, 7h, 63A, IP44, 3P+E
Long Description	Surface Inlet, earthing sleeve position 7h, rated current 63A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Black

### Ordering

E-Number (Sweden)	E2417203
E-Number (Finland)	2417203
E-Number (Norway)	2417203
EAN	7392696675567
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

### Dimensions

Product Net Width	107 mm
Product Net Height	117 mm
Product Net Weight	0.79 kg

---

**Container Information**


---

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	0.87 kg
Package Level 1 EAN	7392696675567
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	128.75 kg
Package Level 2 EAN	7392696073936
Package Level 2 Units	pallet (lift) 125 piece

---



---

**Environmental**


---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---



---

**Certificates and Declarations (Document Number)**


---

CB Certificate	2CHC660163X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

---



---

**Additional Information**


---

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm <sup>2</sup>
Cable Entry Position	Cable entry, M32 alternative rear knock-out cable entry
Color	Black
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Surface inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#363BS7
Mounting Holes	170x95
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TBS
Product Name	Wall mounted inlet
Protection Type	Splashproof

Rated Current ( $I_n$ )	63 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	480 ... 500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Inlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7012 - Basalt Grey

## Classifications

eClass	27440519
UNSPSC	39121406

## Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

