

## PRODUCT-DETAILS

# 463BS1

## Surface inlet, 1h, 63A, IP44, 3P+N+E



### General Information

|                       |                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 463BS1                                                                                                                  |
| Product ID            | 2CMA167574R1000                                                                                                         |
| EAN                   | 7392696675741                                                                                                           |
| Catalog Description   | Surface inlet, 1h, 63A, IP44, 3P+N+E                                                                                    |
| Long Description      | Surface Inlet, earthing sleeve position 1h, rated current 63A, IP44 splashproof, 3-poles+neutral+earth, color code Grey |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417210            |
| E-Number (Finland)     | 2417210             |
| E-Number (Norway)      | 2417210             |
| EAN                    | 7392696675741       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 107 mm |
| Product Net Height | 117 mm |

|                    |         |
|--------------------|---------|
| Product Net Weight | 0.85 kg |
|--------------------|---------|

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 0.94 kg                 |
| Package Level 1 EAN            | 7392696675741           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 137.5 kg                |
| Package Level 2 EAN            | 7392696074001           |
| Package Level 2 Units          | pallet (lift) 125 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660163X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1519130         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                                         |
|------------------------|---------------------------------------------------------|
| Additional Information | 3P+N+E                                                  |
| Ambient Temperature    | -25 ... 40 °C                                           |
| Cable Cross-Section    | 6 ... 25 mm²                                            |
| Cable Entry Position   | Cable entry, M32 alternative rear knock-out cable entry |
| Color                  | Grey                                                    |
| Connection Type        | Screw                                                   |
| Degree of Protection   | IP44                                                    |
| Design                 | Surface mounted plug                                    |
| Frequency (f)          | AC Hz                                                   |
| Function               | Surface Inlet                                           |
| Housing Material       | Plastic (PA)                                            |

|                            |                                  |
|----------------------------|----------------------------------|
| Invoice Description        | Ind. P&S#463BS1                  |
| Mounting Holes             | 170x95                           |
| Number of Poles            | 5                                |
| Order Multiple             | 1 piece                          |
| Product Main Type          | TBS                              |
| Product Name               | Wall mounted inlet               |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 63 A                             |
| Rated Voltage ( $U_r$ )    | Optional voltage V               |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Surface Inlets                   |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC000040M0001                  |
| Installation Manual        | 2CMC000040M0001                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39121406 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

