


PRODUCT-DETAILS

216MHS6

Switched interlocked socket-outlet, 6h, 16A, IP44, 2P+E



General Information

Extended Product Type	216MHS6
Product ID	2CMA167623R1000
EAN	7392696676236
Catalog Description	Switched interlocked socket-outlet, 6h, 16A, IP44, 2P+E
Long Description	Switched Interlocked Socket Outlet, horizontal, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Blue

Ordering

E-Number (Sweden)	E2416812
E-Number (Finland)	2421781
E-Number (Norway)	1564804
EAN	7392696676236
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	168 mm
Product Net Height	116 mm

Product Net Weight	0.58 kg
Mechanical Drawings	9AKK107991A3887

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	0.66 kg
Package Level 1 EAN	7392696676236
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	134.84 kg
Package Level 2 EAN	7392696074025
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1515100
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	6 ... 13 mm
Cable Entry Position	Top and bottom
Cable Outlets Per Side	1xØ25
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz

Function	Switched interlocked socket outlet, horizontal
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#216MHS6
Mounting Holes	146x91
Mounting Type	Horizontal
Number of Poles	3
Order Multiple	1 piece
Product Main Type	CMHS
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	Switched Interlocked
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Suitable For	Switched Interlocked Socket Outlets, Horizontal
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000032M0001
Installation Manual	2CMC000032M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

