

PRODUCT-DETAILS

416MHS2

Industrial Switched Interlocked Socket Outlets, 3P+N+E, 16 A, >50 V



General Information

Extended Product Type	416MHS2
Product ID	2CMA167637R1000
EAN	7392696676373
Catalog Description	Industrial Switched Interlocked Socket Outlets, 3P+N+E, 16 A, >50 V
Long Description	Switched Interlocked Socket Outlet, horizontal, earthing sleeve position 2h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency >300-500 Hz, color code Green

Ordering

E-Number (Sweden)	2416824
E-Number (Finland)	2416824
E-Number (Norway)	2416824
EAN	7392696676373
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	168 mm
Product Net Height	116 mm

Product Net Weight	0.700 kg
--------------------	----------

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	0.7 kg
Package Level 1 EAN	7392696676373
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	141.8 kg
Package Level 2 EAN	7392696074148
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1515100
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	13 ... 17 mm
Cable Entry Position	Top and bottom
Cable Outlets Per Side	1xØ32
Color	Green
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	>300 ... 500 Hz
Function	Outlet
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#416MHS2
Mounting Holes	146x91
Mounting Type	Horizontal
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CMHS
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	Switched Interlocked
Rated Current (I_n)	16 A
Rated Voltage (U_r)	50 ... 500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000032M0001
Installation Manual	2CMC000032M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

