

PRODUCT-DETAILS

# 216MVS6

## Switched interlocked socket-outlet, 6h, 16A, IP44, 2P+E



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | 216MVS6  |
| Product ID            | 2CMA167646R1000  |
| EAN                   | 7392696676465  |
| Catalog Description   | Switched interlocked socket-outlet, 6h, 16A, IP44, 2P+E  |
| Long Description      | Switched Interlocked Socket Outlet, vertical, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Blue |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416829            |
| E-Number (Finland)     | 2421771             |
| E-Number (Norway)      | 1543802             |
| EAN                    | 7392696676465       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 120 mm          |
| Product Net Height  | 149 mm          |
| Product Net Weight  | 0.9 kg          |
| Mechanical Drawings | 9AKK107991A3911 |

---

**Container Information**


---

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 1 kg                    |
| Package Level 1 EAN            | 7392696676465           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 145 kg                  |
| Package Level 2 EAN            | 7392696074193           |
| Package Level 2 Units          | pallet (lift) 125 piece |

---



---

**Environmental**


---

|             |   |
|-------------|---|
| RoHS Status | Following EU Directive 2011/65/EU                     |
| SCIP        | Czech Republic - 4b2a2ca2-9385-463b-8a3a-b3928a138ba9 |

---



---

**Certificates and Declarations (Document Number)**


---

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

---



---

**Additional Information**


---

|                        |  |
|------------------------|--|
| Additional Information | 2P+E   |
| Ambient Temperature    | -25 ... 40 °C                                |
| Cable Cross-Section    | 1.5 ... 4 mm <sup>2</sup>                    |
| Cable Diameter         | 6 ... 13 mm                                  |
| Cable Entry Position   | Top  |
| Cable Outlets Per Side | 1xØ25  |
| Color                  | Blue   |
| Connection Type        | Screw  |
| Degree of Protection   | IP44   |
| Frequency (f)          | 50 Hz<br>60 Hz                               |
| Function               | Switched interlocked socket outlet, vertical |
| Housing Material       | Thermoplastic (PBT)                          |
| Invoice Description    | Ind. P&S#216MVS6                             |
| Mounting Holes         | 171x90                                       |
| Mounting Type          | Vertical                                     |
| Number of Poles        | 3  |
| Order Multiple         | 1 piece                                      |
| Product Main Type      | CMVS   |

|                            |   |
|----------------------------|---|
| Product Name               | Industrial Switched Interlocked Socket Outlet |
| Protection Type            | Switched Interlocked                          |
| Rated Current ( $I_n$ )    | 16 A  |
| Rated Voltage ( $U_r$ )    | 200 ... 250 V                                 |
| Recommended Screw Driver   | PH2   |
| Standards                  | IEC 60309-1, -2, -4                           |
| Suitable For               | Switched Interlocked Socket Outlets, Vertical |
| Suitable for Product Class | IEC Industrial Plugs and Sockets              |
| Instructions and Manuals   | 2CMC000030M0001                               |
| Installation Manual        | 2CMC000030M0001                               |
| RAL Number                 | RAL 7001 - Silver Grey                        |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39121406 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

