

PRODUCT-DETAILS

216MHS12W

Switched interlocked socket-outlet, 12h, 16A, IP67, 2P+E



General Information

Extended Product Type	216MHS12W
Product ID	2CMA167803R1000
EAN	7392696678032
Catalog Description	Switched interlocked socket-outlet, 12h, 16A, IP67, 2P+E
Long Description	Switched Interlocked Socket Outlet, horizontal, earthing sleeve position 12h, rated current 16A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Grey

Ordering

E-Number (Sweden)	2416896
E-Number (Finland)	2416896
E-Number (Norway)	2416896
EAN	7392696678032
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	168 mm
Product Net Height	114 mm
Product Net Weight	0.62 kg

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	0.7 kg
Package Level 1 EAN	7392696678032
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	141.8 kg
Package Level 2 EAN	7392696074766
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
SCIP	Czech Republic - b0b30fc0-3a31-41d5-a35f-56a55306b63f

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1515100
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	6 ... 13 mm
Cable Entry Position	Top and bottom
Cable Outlets Per Side	1xØ25
Color	Grey
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz
Function	Switched interlocked socket outlet, horizontal
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#216MHS12W
Mounting Holes	146x91
Mounting Type	Horizontal
Number of Poles	3
Order Multiple	1 piece
Product Main Type	CMHS
Product Name	Industrial Switched Interlocked Socket Outlet

Protection Type	Switched Interlocked
Rated Current (I _n)	16 A
Rated Voltage (U _r)	Isol. Transformer V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Suitable For	Switched Interlocked Socket Outlets, Horizontal
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000032M0001
Installation Manual	2CMC000032M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

