

## PRODUCT-DETAILS

# 216MVS6W

Switched interlocked socket-outlet, 6h, 16A, IP67, 2P+E



## General Information

|                       |                                                                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 216MVS6W                                                                                                                                                                                       |
| Product ID            | 2CMA167824R1000                                                                                                                                                                                |
| EAN                   | 7392696678247                                                                                                                                                                                  |
| Catalog Description   | Switched interlocked socket-outlet, 6h, 16A, IP67, 2P+E                                                                                                                                        |
| Long Description      | Switched Interlocked Socket Outlet, vertical, earthing sleeve position 6h, rated current 16A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Blue, padlockable in OFF position |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416917            |
| E-Number (Finland)     | 2421776             |
| E-Number (Norway)      | 2416917             |
| EAN                    | 7392696678247       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                   |        |
|-------------------|--------|
| Product Net Width | 120 mm |
|-------------------|--------|

|                     |                 |
|---------------------|-----------------|
| Product Net Height  | 149 mm          |
| Product Net Weight  | 0.93 kg         |
| Mechanical Drawings | 9AKK107991A3918 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 1.04 kg                 |
| Package Level 1 EAN            | 7392696678247           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 150 kg                  |
| Package Level 2 EAN            | 7392696075206           |
| Package Level 2 Units          | pallet (lift) 125 piece |

## Environmental

|             |                                                       |
|-------------|-------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU                     |
| SCIP        | Czech Republic - 8f2a459d-ae21-4edc-8431-c56a61d9e5ef |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                |
|------------------------|----------------|
| Additional Information | 2P+E           |
| Ambient Temperature    | -25 ... 40 °C  |
| Cable Cross-Section    | 1.5 ... 4 mm²  |
| Cable Diameter         | 6 ... 13 mm    |
| Cable Entry Position   | Top            |
| Cable Outlets Per Side | 1xØ25          |
| Color                  | Blue           |
| Connection Type        | Screw          |
| Degree of Protection   | IP67           |
| Frequency (f)          | 50 Hz<br>60 Hz |

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Function                   | Switched interlocked socket outlet, vertical  |
| Housing Material           | Thermoplastic (PBT)                           |
| Invoice Description        | Ind. P&S#216MVS6W                             |
| Mounting Holes             | 171x90                                        |
| Mounting Type              | Vertical                                      |
| Number of Poles            | 3                                             |
| Order Multiple             | 1 piece                                       |
| Product Main Type          | CMVS                                          |
| Product Name               | Industrial Switched Interlocked Socket Outlet |
| Protection Type            | Switched Interlocked                          |
| Rated Current ( $I_n$ )    | 16 A                                          |
| Rated Voltage ( $U_r$ )    | 200 ... 250 V                                 |
| Recommended Screw Driver   | PH2                                           |
| Standards                  | IEC 60309-1, -2, -4                           |
| Suitable For               | Switched Interlocked Socket Outlets, Vertical |
| Suitable for Product Class | IEC Industrial Plugs and Sockets              |
| Instructions and Manuals   | 2CMC000030M0001                               |
| Installation Manual        | 2CMC000030M0001                               |
| RAL Number                 | RAL 7001 - Silver Grey                        |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

