

PRODUCT-DETAILS

232MHS9W

Switched interlocked socket-outlet, 9h, 32A, IP67, 2P+E



General Information

| | |
|-----------------------|--|
| Extended Product Type | 232MHS9W |
| Product ID | 2CMA167849R1000 |
| EAN | 7392696678490 |
| Catalog Description | Switched interlocked socket-outlet, 9h, 32A, IP67, 2P+E |
| Long Description | Switched Interlocked Socket Outlet, horizontal, earthing sleeve position 9h, rated current 32A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Red |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | 2416941 |
| E-Number (Finland) | 2416941 |
| E-Number (Norway) | 2416941 |
| EAN | 7392696678490 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 168 mm |
| Product Net Height | 129 mm |
| Product Net Weight | 0.7 kg |

Container Information

| | |
|--------------------------------|-------------------------|
| Package Level 1 Width | 135 mm |
| Package Level 1 Depth / Length | 140 mm |
| Package Level 1 Height | 200 mm |
| Package Level 1 Gross Weight | 0.8 kg |
| Package Level 1 EAN | 7392696678490 |
| Package Level 1 Units | box 1 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 159.2 kg |
| Package Level 2 EAN | 7392696075039 |
| Package Level 2 Units | pallet (lift) 174 piece |

Environmental

| | |
|-------------|---|
| RoHS Status | Following EU Directive 2011/65/EU |
| SCIP | Czech Republic - 29b5dc42-ed9d-4bb0-8a47-9cf5c1c33576 |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000057M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1515100 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|--|
| Additional Information | 2P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 2.5 ... 10 mm ² |
| Cable Diameter | 13 ... 21.5 mm |
| Cable Entry Position | Top and bottom |
| Cable Outlets Per Side | 1xØ25 |
| Color | Red |
| Connection Type | Screw |
| Degree of Protection | IP67 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Switched interlocked socket outlet, horizontal |
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | Ind. P&S#232MHS9W |
| Mounting Holes | 146x91 |
| Mounting Type | Horizontal |
| Number of Poles | 3 |
| Order Multiple | 1 piece |
| Product Main Type | CMHS |

| | |
|----------------------------|---|
| Product Name | Industrial Switched Interlocked Socket Outlet |
| Protection Type | Switched Interlocked |
| Rated Current (I_n) | 32 A |
| Rated Voltage (U_r) | 380 ... 415 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2, -4 |
| Suitable For | Switched Interlocked Socket Outlets, Horizontal |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC000032M0001 |
| Installation Manual | 2CMC000032M0001 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 12 ... 10 AWG |
| Tightening Torque | WireClamp1.2 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

