

PRODUCT-DETAILS

432MVS2W

Switched interlocked socket-outlet, 2h, 32A, IP67, 3P+N+E



General Information

Extended Product Type	432MVS2W
Product ID	2CMA167885R1000
EAN	7392696678858
Catalog Description	Switched interlocked socket-outlet, 2h, 32A, IP67, 3P+N+E
Long Description	Switched Interlocked Socket Outlet, vertical, earthing sleeve position 2h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 300-500 Hz, color code Green

Ordering

E-Number (Sweden)	2416987
E-Number (Finland)	2416987
E-Number (Norway)	2416987
EAN	7392696678858
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	120 mm
Product Net Height	149 mm
Product Net Weight	0.76 kg
Mechanical Drawings	9AKK107991A3923

Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	0.85 kg
Package Level 1 EAN	7392696678858
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	126.25 kg
Package Level 2 EAN	7392696075572
Package Level 2 Units	pallet (lift) 125 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
SCIP	Czech Republic - 03dd4506-f81e-4d23-828f-1ac572f23d30

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Top
Cable Outlets Per Side	1xØ25
Color	Green
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	>300 ... 500 Hz
Function	Switched interlocked socket outlet, vertical
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#432MVS2W
Mounting Holes	171x90
Mounting Type	Vertical
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CMVS
Product Name	Industrial Switched Interlocked Socket Outlet

Protection Type	Switched Interlocked
Rated Current (I _n)	32 A
Rated Voltage (U _r)	50 ... 500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Sub-Function	Cable entry, knock-outs Ø25mm
Suitable For	Switched Interlocked Socket Outlets, Vertical
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000030M0001
Installation Manual	2CMC000030M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

