
PRODUCT-DETAILS

463MHS4W

Switched interlocked socket-outlet, 4h, 63A, IP67, 3P+N+E



General Information

Extended Product Type	463MHS4W
Product ID	2CMA167904R1000
EAN	7392696679046
Catalog Description	Switched interlocked socket-outlet, 4h, 63A, IP67, 3P+N+E
Long Description	Switched Interlocked Socket Outlet, horizontal, earthing sleeve position 4h, rated current 63A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Yellow

Ordering

E-Number (Sweden)	2417013
E-Number (Finland)	2417013
E-Number (Norway)	2417013
EAN	7392696679046
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	206 mm
Product Net Height	168 mm

Product Net Weight	1.9 kg
--------------------	--------

Container Information

Package Level 1 Width	180 mm
Package Level 1 Depth / Length	215 mm
Package Level 1 Height	180 mm
Package Level 1 Gross Weight	2.3 kg
Package Level 1 EAN	7392696679046
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	213.2 kg
Package Level 2 EAN	7392696075763
Package Level 2 Units	pallet (lift) 84 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm ²
Cable Diameter	17 ... 35 mm
Cable Entry Position	Top and bottom
Cable Outlets Per Side	1xØ32
Color	Yellow
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Switched interlocked socket outlet, horizontal
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#463MHS4W
Mounting Holes	152x132
Mounting Type	Horizontal
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CMHS
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	Switched Interlocked
Rated Current (I_n)	63 A
Rated Voltage (U_r)	57/100 ... 75/130 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Sub-Function	Cable entry, knock-outs 2xØ32mm
Suitable For	Switched Interlocked Socket Outlets, Horizontal
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000031M0001
Installation Manual	2CMC000031M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

