

PRODUCT-DETAILS

332MM9

Switched interlocked socket-outlet, 9h, 32A, IP44, 3P+E



General Information

Extended Product Type	332MM9
Product ID	2CMA167995R1000
EAN	7392696679954
Catalog Description	Switched interlocked socket-outlet, 9h, 32A, IP44, 3P+E
Long Description	Switched Interlocked Socket Outlet, metal, earthing sleeve position 9h, rated current 32A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Blue

Ordering

E-Number (Sweden)	2417073
E-Number (Finland)	2417073
E-Number (Norway)	2417073
EAN	7392696679954
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	135 mm
Product Net Height	135 mm
Product Net Weight	1.4 kg

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	1.48 kg
Package Level 1 EAN	7392696679954
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	277.52 kg
Package Level 2 EAN	7392696075824
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
SCIP	Czech Republic - bf8039cc-4bf7-4196-9c50-b7eab2414f89

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1515100
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Entry Position	Top and bottom
Cable Outlets Per Side	1xM25+1xM32
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Switched Interlocked Socket Outlet, metal
Housing Material	Aluminium
Invoice Description	Ind. P&S#332MM9
Mounting Holes	165x91
Mounting Type	Vertical
Number of Poles	4
Order Multiple	1 piece
Product Main Type	CMM
Product Name	Industrial Switched Interlocked Socket Outlet

Protection Type	Switched Interlocked
Rated Current (I_n)	32 A
Rated Voltage (U_r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Sub-Function	Cable entry, 2xM25+2xM32
Suitable For	Switched Interlocked Socket Outlets in Metal
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000034M0001
Installation Manual	2CMC000034M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp 1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets in Metal

