

## PRODUCT-DETAILS

# 332MM11

## Switched interlocked socket-outlet, 11h, 32A, IP44, 3P+E



### General Information

|                       |                                                                                                                                                              |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 332MM11                                                                                                                                                      |
| Product ID            | 2CMA167997R1000                                                                                                                                              |
| EAN                   | 7392696679978                                                                                                                                                |
| Catalog Description   | Switched interlocked socket-outlet, 11h, 32A, IP44, 3P+E                                                                                                     |
| Long Description      | Switched Interlocked Socket Outlet, metal, earthing sleeve position 11h, rated current 32A, IP44 splashproof, 3-poles+earth, frequency 60 Hz, color code Red |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2417075             |
| E-Number (Finland)     | 2417075             |
| E-Number (Norway)      | 2417075             |
| EAN                    | 7392696679978       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 135 mm |
| Product Net Height | 135 mm |

|                    |        |
|--------------------|--------|
| Product Net Weight | 1.4 kg |
|--------------------|--------|

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 135 mm                  |
| Package Level 1 Depth / Length | 140 mm                  |
| Package Level 1 Height         | 200 mm                  |
| Package Level 1 Gross Weight   | 1.4 kg                  |
| Package Level 1 EAN            | 7392696679978           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 263.6 kg                |
| Package Level 2 EAN            | 7392696075848           |
| Package Level 2 Units          | pallet (lift) 174 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1515100         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                           |
|------------------------|-------------------------------------------|
| Additional Information | 3P+E                                      |
| Ambient Temperature    | -25 ... 40 °C                             |
| Cable Cross-Section    | 2.5 ... 10 mm <sup>2</sup>                |
| Cable Entry Position   | Top and bottom                            |
| Cable Outlets Per Side | 1xM25+1xM32                               |
| Color                  | Red                                       |
| Connection Type        | Screw                                     |
| Degree of Protection   | IP44                                      |
| Frequency (f)          | 60 Hz                                     |
| Function               | Switched Interlocked Socket Outlet, metal |
| Housing Material       | Aluminium                                 |
| Invoice Description    | Ind. P&S#332MM11                          |

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Mounting Holes             | 165x91                                        |
| Mounting Type              | Vertical                                      |
| Number of Poles            | 4                                             |
| Order Multiple             | 1 piece                                       |
| Product Main Type          | CMM                                           |
| Product Name               | Industrial Switched Interlocked Socket Outlet |
| Protection Type            | Switched Interlocked                          |
| Rated Current ( $I_n$ )    | 32 A                                          |
| Rated Voltage ( $U_r$ )    | 440 ... 460 V                                 |
| Recommended Screw Driver   | PH2                                           |
| Standards                  | IEC 60309-1, -2, -4                           |
| Sub-Function               | Cable entry, 2xM25+2XM32                      |
| Suitable For               | Switched Interlocked Socket Outlets in Metal  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets              |
| Instructions and Manuals   | 2CMC000034M0001                               |
| Installation Manual        | 2CMC000034M0001                               |
| RAL Number                 | RAL 7001 - Silver Grey                        |

## Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39121406 |

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets in Metal

