

PRODUCT-DETAILS

3125MM7

Switched interlocked socket-outlet, 7h, 125A, IP44, 3P+E



General Information

Extended Product Type	3125MM7
Product ID	2CMA168049R1000
EAN	7392696680493
Catalog Description	Switched interlocked socket-outlet, 7h, 125A, IP44, 3P+E
Long Description	Switched Interlocked Socket Outlet, metal, earthing sleeve position 7h, rated current 125A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Black

Ordering

E-Number (Sweden)	E2417118
E-Number (Finland)	2421382
E-Number (Norway)	2417118
EAN	7392696680493
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	230 mm
Product Net Height	221 mm
Product Net Weight	7.9 kg

Container Information

Package Level 1 Width	235 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Height	245 mm
Package Level 1 Gross Weight	7.9 kg
Package Level 1 EAN	7392696680493
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	185.9 kg
Package Level 2 EAN	7392696076371
Package Level 2 Units	pallet (lift) 21 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 70 mm²
Cable Entry Position	Top and bottom
Cable Outlets Per Side	4xM50
Color	Black
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Switched Interlocked Socket Outlet, metal
Housing Material	Aluminium
Invoice Description	Ind. P&S#3125MM7
Mounting Holes	1819944
Mounting Type	Vertical
Number of Poles	4
Order Multiple	1 piece
Product Main Type	CMM
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	Switched Interlocked
Rated Current (I _n)	125 A

Rated Voltage (U _r)	480 ... 500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Sub-Function	Cable entry, 2xM50
Suitable For	Switched Interlocked Socket Outlets in Metal
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000044M0001
Installation Manual	2CMC000044M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	3 ... 1 AWG
Tightening Torque	WireClamp5.6 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets in Metal

